

mPDF

Example 57. New mPDF v5-3 active forms b

```
<?php

include("../mpdf.php");

$mpdf=new mPDF('');

//=====

$html = '
<style>
textarea {
}
input {
}
select {
    font-family: arialunicodems
}
</style>
<body>
<h2>Active Forms</h2>

<form action="http://127.0.0.1/MPDF1.com/common/mpdf/examples/formsubmit.php" method="post">
<b>Input Text</b>
<input type="text" size="90" name="inputfield" value="" title="The title attribute works like a tool-tip" />
<br /><br />

<b> Readonly </b>
<input type="text" size="90" name="readonlyfield" value="Read-only field. The value will be exported on submit" title="The title does not do anything if the field is read-only" readonly="readonly" />
<br /><br />

<b> Disabled </b>
<input type="text" size="90" name="disabledfield" value="Disabled field. The value will not be exported on submit" title="The title does not do anything if the field is disabled." disabled="disabled" />
<br /><br />

<b> Required </b>
<input type="text" size="90" name="requiredfield" value="" title="This field must be entered before you can submit." required="required" />
<br /><br />

<b> Hidden </b>
<input type="hidden" name="hiddenfield" value="value_of_hidden_field">
<br /><br />

<b> Input Password </b>
<input type="password" size="40" name="password" value="mysecretpassword" title="This field is set to act as a password field." />
<br /><br />

<b> Calculations </b>
<input type="text" size="20" name="maths1" value="0" onChange="var a = this.getField('maths1').value;
var b = this.getField('maths2').value;
this.getField('maths3').value = a + b;
" /> +
<input type="text" size="20" name="maths2" value="0" onChange="var a = this.getField('maths1').value;
var b = this.getField('maths2').value;
this.getField('maths3').value = a + b;" />
```



```

<input type="radio" name="num_languages" value="1" checked="checked" > One &nbsp;&nbsp;&nbsp;
<input type="radio" name="num_languages" value="2" > Two &nbsp;&nbsp;&nbsp;&nbsp;
<input type="radio" name="num_languages" value="3" > Three &nbsp;&nbsp;&nbsp;&nbsp;
<input type="radio" name="num_languages" value="4" > Four &nbsp;&nbsp;&nbsp;&nbsp;
<input type="radio" name="num_languages" value="5" > Five +
<br /><br />

<input type="checkbox" name="email" value="email_subscrbe" checked="checked" /> Please send me regular
information by e-mail<br>
<input type="checkbox" name="phone" value="phone-me" disabled="disabled" /> Please phone me (not
available at present)<br>
<input type="checkbox" name="subscribe" value="newsletter_subscribe" /> Please subscribe me to the
Newsletter
<br /><br />

<br /><br />

Click this button to see Javascript in action:
<input type="image" name="imageButton" value="imagesubmitted" src="goto.gif" title="Click to run
javascript" onClick="
var npass = this.getField('\\password\\').value;
app.alert('\\Value of password field is: \\\\' + npass + '\\\\\'');
var nButton = app.alert({
cMsg: '\\Do you want to change the input text field to: T\u00f6rkylempij\u00e4?',
cTitle: '\\A message from A. C. Robat\\',
nIcon: 2, nType: 2
});
if ( nButton == 4 ) {
this.getField('\\inputfield\\').value = '\\T\u00f6rkylempij\u00e4\\';
}
" />

<br /><br />

<input type="submit" name="disabled_submit" value="Disabled" disabled="disabled" title="This Submit
button is disabled" />

<input type="reset" name="resetfield" value="Reset" />

<input type="submit" name="submit" value="Submit" title="Click here to submit" />

<input type="submit" name="submit_in_Turkish" value="Submit (T&#252;rk&#231;e)" title="Click here to
submit in T&#252;rk&#231;e" />

<input type="button" name="javascriptButton" value="Javascript Button" onClick="
var npass = this.getField('\\password\\').value;
app.alert('\\Value of password field is: \\\\' + npass + '\\\\\'');
var nButton = app.alert({
cMsg: '\\Do you want to change the input text field to: T\u00f6rkylempij\u00e4?',
cTitle: '\\A message from A. C. Robat\\',
nIcon: 2, nType: 2
});
if ( nButton == 4 ) {
this.getField('\\inputfield\\').value = '\\T\u00f6rkylempij\u00e4\\';
}
" />
<br /><br />

</form>
';

//=====
if ($_REQUEST['html']) { echo $html; exit; }
if ($_REQUEST['source']) {
    $file = __FILE__;
    header("Content-Type: text/plain");
}

```

```

header("Content-Length: ". filesize($file));
header("Content-Disposition: attachment; filename='".$file."'");
readfile($file);
exit;
}

//=====
$mpdf->useActiveForms = true;

/*
// Try playing around with these (these are also in config.php)
$mpdf->formUseZapD = false;
$mpdf->formSubmitNoValueFields = true;

$mpdf->formExportType = 'xfdf'; // 'html' or 'xfdf'
$mpdf->formSelectDefaultOption = true; // for Select drop down box; if no option is explicitly maked
as selected,                                     // this determines whether to select 1st option (as per
                                                 // - affects whether "required" attribute is relevant
$mpdf->form_border_color = '0.0 0.820 0.0';
$mpdf->form_background_color = '0.941 0.941 0.941';
$mpdf->form_border_width = '1';
$mpdf->form_border_style = 'S';

$mpdf->form_radio_color = '0.0 0.820 0.0';
$mpdf->form_radio_background_color = '0.941 0.5 0.5';

$mpdf->form_button_border_color = '0.0 0.820 0.0';
$mpdf->form_button_background_color = '0.941 0.941 0.941';
$mpdf->form_button_border_width = '1';
$mpdf->form_button_border_style = 'S';
*/
$mpdf->WriteHTML($html);

//=====
// JAVASCRIPT FOR WHOLE DOCUMENT
$mpdf->SetJS('
var dialogTitle = "Enter details";
var defaultAnswer = "";
var reply = app.response("This is javascript set to run when the document opens. Enter value for first
field", dialogTitle, defaultAnswer);
if (reply != null) {
this.getField("inputfield").value = reply;
}
');

//=====
// OUTPUT
$mpdf->Output(); exit;

//=====
//=====
//=====
//=====

?>
```